



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PV700HF

PowerVerter Ultra-Compact Inverter - Portable Power for All Applications



Highlights

- 700W continuous output; 1400W peak output (instantaneous)
- Converts 12V DC (battery) power into 110-120V AC (household) power; 3 AC outlets
- Installs in minutes (integrated mounting feet included)
- Provides a quiet alternative to generator noise and fumes
- Includes "battery saver" low voltage alarm/shutdown

Description

Harness your vehicle's battery to efficiently power appliances, small electronics and office equipment on the road. Continuously supplies up to 700W of 120V AC power to 3 AC outlets from any 12V battery. Featuring an ultra-compact, lightweight design with metal housing, the PV700HF is among the smallest, most rugged inverters available.

Applications

- Ideal for portable electronics, office equipment, RV and mobile appliances, video game and small entertainment systems, battery chargers, and more

Package Includes

- PV700HF Ultra-Compact DC-to-AC Inverter
- Instruction manual with warranty information

Features

- Provides 120V AC power for a variety of mobile applications
- 700W continuous output power; 1400W peak output power (instantaneous)
- 3 AC outlets
- Ultra-compact extruded aluminum housing stands up to the toughest environments
- Cooling fan lengthens inverter service life & maintains cool operation
- Integrated mounting feet assure safe fixed installation
- Low battery alarm/shutdown detects low battery voltage and shuts down inverter
- Overload alarm/shutdown detects wattage overload on inverter outlets and shuts down inverter as a protective measure
- DC input terminals provide a solid connection to battery with user-supplied cables
- Lighted on/off switch shows inverter operations in cramped or dark environments

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	Compatible with 12V DC automotive or battery power sources

Frequency compatibility	60 Hz
OUTPUT	
Output watts	700W (continuous)/1400W (peak)
Output nominal voltage	120V
Output voltage regulation	Maintains PWM sine wave output voltage of 115 V AC (+/- 8 V AC)
Output frequency regulation	60 Hz (+/- 3 Hz)
Outlet quantity / type	3 x NEMA 5-15R
Continuous output capacity (watts)	700
Peak output capacity (watts)	1400
INPUT	
Input connection type	Set of 2 DC bolt-down wiring terminals
Input cord length	User supplies cabling. Minimum gauges for full load operation: 6 gauge or larger (see instruction manual)
Recommended electrical service	Requires 12V DC input source capable of delivering 80A for the required duration (when used at full capacity). For automotive applications, professional hardwire installation with 125A battery system fusing is recommended
Maximum input amps / watts	Full continuous load - 80A at 12V DC, No load - 0.95A at 12V DC, Shutdown - 150 micro amps
BATTERY	
DC system voltage	12V
LEDS ALARMS & SWITCHES	
Alarms	Dual-function alarm indicates overload conditions or low DC input voltage of 10.5V or less
Switches	Lighted on/off power switch
PHYSICAL	
Shipping weight (lbs)	3.5
Shipping weight (kg)	1.6
Shipping Dimensions (HWD/in)	4 x 6.25 x 10.25
Shipping Dimensions (HWD/cm)	10.2 x 16 x 26
Unit weight (lbs)	2.8
Unit weight (kg)	1.26
Unit Dimensions (HWD/in)	2.76 x 5 x 8.17
Unit Dimensions (HWD/cm)	7 x 12.7 x 21
Material of construction	Aluminum/sheet metal
Cooling method	Fan
ENVIRONMENTAL	
Relative Humidity	0-95% non-condensing
WARRANTY	
Product warranty	1 year (outside the U.S. and Canada, call for warranty information)
SPECIAL FEATURES	
TVSS grounding	Main grounding screw for connecting inverter to earth, vehicle, or boat grounding systems

Appearance

Attractive metallic gray color scheme

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=3610.

©2008 Tripp Lite. All Rights Reserved.