

## 2088 Series Diaphragm Pump Automatic Demand Pump (115 VAC)



Premium Pump w/ cooling fins

Standard

Model	2088-594-154			
Description	3.3 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports (1/2" - 14 National American Straight Pipe Thread, requires SHURflo swivel type fittings), Poly Housing			
Voltage	115 VAC			
PSI	10	20	30	40
BAR	0.7	1.4	2.1	2.8
GPM	2.60	2.34	2.08	1.85
L/min	9.8	8.8	7.9	7.0
Amps	0.58	0.67	0.76	0.85

\* Additional technical information is available below in PDF format.  
Adobe Acrobat Reader is required to view these documents.

[Product Data Sheet](#) | [Troubleshooting](#) | [Replacement Parts](#)

[close window](#) ▶



SHURflo Pump Manufacturing Company  
5900 Katella Ave  
Cypress, Ca 90630  
Phone: 562-795-5200 or 800-854-3218  
Fax: 562-795-7564  
E-mail: [customer\\_service@shurflo.com](mailto:customer_service@shurflo.com) or [literature@shurflo.com](mailto:literature@shurflo.com)

© 2002 SHURflo Pump Manufacturing Company. All Rights Reserved